Annual symposium on the theme "Post-mining risk management in the Netherlands": Dealing with Post-Mining-Hazards From theoretical approach to practical remediation



Stichting I.A.E.G. 1990 Werkgroep Ingeokring P.O. Box 5048, NL-2600 GA Delft The Netherlands




Dr. rer. nat. Johannes Klünker Ingenieurbüro Heitfeld - Schetelig GmbH Beratende Geologen und Ingenieure Jean-Bremen-Straße 1-3, 52080 Aachen




# Na ijlende gevolgen steenkolenwinning Zuid-Limburg (GS-ZL) Collected documents















high

# Effects not dependent on mine water rise

Effect 1: Historical mine shafts

Industrial mine shafts

Effect 2: Voids due to historical near-surface mining

Voids due to industrial mining near top of Carboniferous and Upward Drillings


- Effect 3: Change of groundwater quality/quantity
- Effect 4: Differential ground heave
- Effect 5: Accumulation of mine gas
- Effect 6: Induced earthquakes

low



# General map of the project areas


















- Identification of 59 historical shafts in the area of Kerkrade, all impact category EK 1 ("red")
- For all shafts depiction of the "Accuracy of position" and of the "Shaft-Protection-Zone"
- > Awareness-raising
- Management of existing risks and avoid the creation of new risks
- Strict regulations on new construction buildings
- Prospecting and investigating of all 59 shafts
- Remediation measures as far as necessary



## **Shaft-Protection-Zones in Kerkrade**








# Safety check of industrial mine shafts










Impact cate- gory	Relative proba- bility of occur- rence	Shaft	Suggested action
EK 1	High	-	
EK 2	Medium	Melanie	Investigation of current situation and remediation measures in the short-term
		Buizenschacht, Willem I/II (Domaniale), Beerenbosch I, Neuland	
EK 3	Low	Willem I (Willem Sophia), Julia I / II, Louise	Periodic monitoring of the backfilling collumn based on the current surface use
		Willem II (Willem Sophia), Baamstraat, Sophia, Oranje Nassau (7 shafts), Wilhelmina I / II, Emma I-IV, Hendrik I-IV, Maurits I-III, Catharina, Laura I / II	
EK 4	None	Nulland, Ham II	Periodic monitoring
		Beerenbosch II	



# Map of industrial mine shafts









- Identification of 39 industrial shafts
- Status concerning safety is mostly sufficient
- Only 6 industrial shafts do not completely comply with the actual state of the art
- Monitoring is necessary, partly a facility/access for monitoring has to be (re-)established
- > 6 industrial shafts need investigation and maybe enhanced remediation






- > Main coal seam, mineable coal seam or not mineable coal seam
- > Dip at high angle (≥ 40 gon) or low angle (≤ 40 gon)
- > Evidence of near surface mining in documents
- Indication of mining activities above the uppermost gallery
- Documentation of sinkholes in the past




# Potential impact areas from near-surface mining in the historical mining area















## Industrial near surface mining Definition of potential impact areas














## Voids due to industrial near-surface mining Map of the potential impact areas in project areas 2/3










- Historical mining in the area of Kerkrade mostly of impact category EK 2 ("yellow") and EK 3 ("blue")
- Industrial mining mostly of impact category EK 3 ("blue")
- 26 patches of impact category EK 1 ("red") and EK 2 ("yellow")
- Pre-active measures on existing situation are disproportional
- > Awareness-raising
- Management of existing risks and avoid the creation of new risks
- Strict regulations on new construction buildings



# **General map of Upward and Downward Drillings**








# **Detailed map of Upward and Downward Drillings**









# Step 1:

Detailed georeferentiation of mining maps on actual topography

Step 2

- Preliminary investigations by small hammer drivings
- Vertical small hammer drivings in a grid pattern of i.e. 3 x 3 m
- Meanwhile first test of inclined small hammer drivings



# Investigation of shaft location by inclined hammer drivings








# Core material out of an old shaft in small hammer drivings









# Step 3

# Investigation of larger depths by inclined core drillings



# Core drilling rig inside a courtyard







# Positioning of core drilling rig behind buildings







# Investigation of old shaft near train line








# Shaft remediation by re-filling partially with cohesive material








# Shaft Remediation by concrete slab on rock surface







# Shaft remediation by re-filling partially with cohesive material (including clay sealing)








# Shaft remediation by injection of the loose shaft fill material







# Shaft remediation by injection of loose shaft fill material







## Setting up the construction site for remediation measures at DOM 27 and DOM 28








# **Equipment for cement injections**












# **Equipment for cement injections**














# Injected cement [t solid weight] vs depth [m]







## **Injected cement vein**





